
ILUMA® CBCT Scanner Specifications

ILUMA CBCT Scanner	ILUMA LFOV	ILUMA SFOV	
Plate Dimensions:	24.4 x 19.5cm - horizontal	13 x 13cm - horizontal	
Volume of Reconstruction:	(cylindrical) up to 21.1 x 14.2cm	(cylindrical) up to 10.8 x 9.6cm	
X-ray Source:	High Frequency, constant potential, 120 kVp, 1- 3.8 mA	Same	
Focal Spot:	0.3mm	Same	
Image Detector:	Amorphous Silicon Flat Panel	Same	
Pixel Pitch	127 micron (0.005 inch)	Same	
Software OS:	Windows XP Pro	Same	
Workstation:	Quadl Core Pentium 64 bit processor	Same	
Gray Scale:	16 bit (16,384 gray scales)	Same	
Voxel Size:	Selectable:		
	Standard - 0.4mm	Same	
	Normal - 0.3mm	Same	
	High - 0.2mm	Same	
	Ultra High - 0.09mm	Same	
Image Acquisition:	Cone beam tomography geometry - single 360° rotation		
Scan Time:	Variable scan times between 20 - 40 seconds in a single 360° rotation and 7.8 seconds in a single 190° rotation		
Patient Position:	Seated with rear head stabilization and chin support		
Reconstruction Type:	3D		
Reconstruction Time:	2 minutes ar greater, depending an volume & resolution to be constructed		
System Footprint:	42" × 56"		
System Weight:	350 kg (770 lbs)		
Recommended Room Size:	8' x 8' x 8' (l x w x h)		
Minimum Room Size:	6' x 7' x 8' () x w x h)		

ILUMA® CBCT Scanner Dimensions/Footprint

The ILUMA CBCT Scanner is delivered as a complete package including software, computer, dual monitors, installation, training, delivery and a 3 or 5 year warranty.



Orders and Customer Service: 800-879-9799 or 550-223-4455 Convestic Fac: 800-986-9574 or 580-223-4561 www.lumact.com Copyright 2008 MTEC, a 3M Company

>lemed Das Systemhaus für die Medizin

ic med GmbH IC med GmDH Walther-Rathenau-Str. 4 D-06116 Halle/Saale Tel.: +49 (0) 345-298419-30 Fax: +49 (0) 345-298419-60 www.ic-med.de





IMTEC Corporate Office IMTEC PLAZA 2401 North Commerce Ardmore, Oklahoma 73401, USA Tel: 580-223-4456 Toll Free: 800-879-9799

IMTEC United Kingdom Ltd. 23 Clement Drive Crewe. Cheshire CW13GN Tel: +44-844-800-8983 Fax: +44-781-391-1372

Fax: 580-223-4561 International

Fax: 800-986-9574 U.S.

IMTEC Los Alamos

HYTEC Technology Center 110 Eastgate Drive Los Alamos, New Mexico 87544, USA Tel: 505-661-3000 Fax: 505-662-5179

Cuernavaca, Morelos Mexico 62290 Tel: +52-(01)-777-316-4464 Toll Free: 01-800-006-4464 Fax: +52-(01)-777-316-0790 IMTEC Canada 8000 Jane St. Suite 202

Rio Mayo 1219

Col. Vista Hermosa

Fax: 905-660-1905 IMTEC Europa Dornbachstraße 30

61440 Oberursel



IMTEC Latinoamérica, S.A. DE C.V.

Germany Tel: +49 6171 88798-27 Toll Free: 00800 46833-000 Fax: +49 6171 88798-20



ЗМ

PM168 Rev03

IMTEC

ЗМ

The All-in-One Radiographic Machine




The ILUMA® CBCT Scanner provides all the necessary information to diagnose and treat patients with better resolution than ever before, using the latest generation in Cone Beam Computed Tomography to produce advanced state-of-the-art images. When using the ILUMA CBCT Scanner, clinicians have the accurate anatomic information to plan treatment procedures from multiple reconstructions of patient data. The ILUMA CBCT Scanner delivers extremly accurate images in as little as two seconds with images comparable to Medical CTs with much less radiation doses.

IMTEC's ILUMA CBCT Scanner is a compact scanner designed for use in imaging centers, dental, medical offices and ENT offices, hospitals and universities around the world.

- Orthodontic, Maxillofacial and ENT applications
- Patient/Study database
- Full Volume or Volume of Interest Rendering
- Ultra-thin CT slices (with a resolution as high as 0.09mm)
- Panoramic and 2D radiographic images
- Offers up to 21.1cm x 14.2cm (cylindrical) Volume of Reconstruction Amorphous Silicon Flat Panel Sensor Plates
- Treatment planning & simulation software: ILUMAVision .
- . MIP, Mini IP, Faded Mip MPR Ray Sum Rendering
- Cross-sectional viewing
- Powerful Segmentation tools
- Inner Vision
- 1:1 scale images
- Report Generator
- . Measurument tools
- · Export to DICOM 3 (Compatible with 3rd Party software and systems)
- PACS interface

DigiGuide™ MDI Drill Guide



DigiGuide™ MDI Drill Guide - Implant Placement

Features of DigiGuide™ MDI Software include the ability to map the inferior alveolar nerve. The software also provides a panoramic X-ray for mesiodistal spacing evaluation and sagittal slices for evaluation of buccolingual width at any location in the arch. DigiGuide™ MDI also provides the ability to evaluate the orientation and thickness of an existing denture at any location in the arch. This leads to more informed case selection and surgical planning which results in simpler, safer and quicker MDI surgeries as well as fewer complications when retrofitting an existing denture.

Key Features of ILUMA® CBCT Scanner

		Elite SFOV	
Worklist Modality		х	х
ILUMAView CD	×	х	×
High Performance Reconstructor		х	х
ncreased Storage Capacity		х	х
LUMAVision Elite Package		х	х
Small Field-of-View (SFOV)		х	
Large Field-of-View (LFOV)	×		х

ILUMA Elite CBCT Scanner


The ILUMA Eite CBCT Scanner offers faster image reconstruction than ever before. This clear advantage for a practice means higher patient throughput resulting in enhanced profitability. Quality of data generated by the Elite is another benefit for growing a prosperous, reputable practice. The Elite is an integral tool for a clinician's success.








Information at your fingertips



High Quality 3D Volume Rendering - Coronal, Axial and Sagittal

The ILUMA simplifies the process of evaluating treatment planning and achieving successful treatment procedures. Obtaining images powered by FlashCT[®] Technology in-office increases the likelihood of a proposed treatment plan being accepted by the patient. All rendering can occur at the clinician's office making the information readily available.



Cross Section Viewing Bone Density

Service & Technical Support

IMTEC's Technical Support Team is committed to delivering outstanding service. Because IMTEC promises support when you need it, after hours support is available at no additional cost. Certified field technicians are also available for situations that cannot be resolved over the telephone. For more customer service and technical support information please contact our offices at 800-879-9799 for more information.

Orders and Customer Service: 800-879-9799 or 580-223-4656 Domestic Fax: 800-986-9574 or 580-223-4561 www.iumact.com Copyright 2008 MTEC, a 3M Company

Orders and Customer Service: 800-879-9799 or 580-223-4456 Domestic Fax: 800-986-9574 or 580-223-4561 www.lumact.com Copyright 2008 IMTEC, a SM Company

Orders and Customer Service: 800-879-9799 or 880-223-4456 Domestic Fax: 800-986-9674 or 580-223-4561 www.lumact.com Copyright 2008 IMTEC, a SM Company